























# ONYX

TECHNOLOGY POWERING A CLEANER FUTURE

## Service Data Sheet LX600 603cc Engine

Power	Displacement	Compression	Oil capacity	Valve Clearance Intake	Valve Clearance Exhaust	Plug type	Plug gap	Ignition coil air gap	Oil filter
									
(Hp)	(cc)	(-)	(l)	(mm) cold	(mm) cold	NGK (code)	(mm)	(mm)	(code)
17	603	8.1:1	1.5	0.10 - 0.15	0.10 - 0.15	BPR4ES	0.7 - 0.8	0.2 - 0.4	K49065-0721

Air filter		Compression	Ring end gap	Cylinder bore	Cylinder head	Con rod	Flywheel	Crankcase cover	Intake manifold	Oil drain plug
										
(code) pre filter	(code) main filter	min (kPa)	max (mm)	max (mm)	(Nm)	(Nm)	(Nm)	(Nm)	(Nm)	(Nm)
K11013-7046	K11013-0752	448	0.7	73.1	27.4	9.8	56	27.4	5.9	6.9

Spark plug	Valve clearance lock nut	General					Workshop Manual P/No.	Fuel	Oil Type
		M4	M5	M6	M8	M10			
		M4	M5	M6	M8	M10			
(Nm)	(Nm)	(Nm)	(Nm)	(Nm)	(Nm)	(Nm)			
22	11	2	3.4	5.9	15	20	99924-2094-03	LPG Propane-Vapor Cylinder Only	SJ or higher class SAE40, SAE30, SAE10W-30/SAE10W-40, or SAE5W-20 (1.7l with new filter)