

ONYX™



PRODUCT
CATALOG

THE FUTURE STARTS WITH YOU

Table of Contents

Our Vision, Mission and Soul	03
Floor Scrubbers	04-05
Rotary Floor Scrubbers	06-07
Cylindrical Scrubbers	08-09
Lithium-ion Power	10-11
SXi Configurations	12-13
Propane Floor Machines	14-15
Propane Floor Machines	16-17
HERO	18-21
TX1 Low Speed Floor Machine	22-23
R25 Wet Dry Vacuum	24-25

Our Vision

We believe that tomorrow can, and will, be better than today. But, it won't happen on its own. The future starts with you.

Our Mission

Our mission is to deliver fast, simple, reliable products that empower you to become your best.

Our Soul

We are real people with a drive to solve real problems. No fluff. No frills. We show up with grit, heart, and hustle, and we believe that helping you become your best allows us to do the same.

FLOOR SCRUBBERS

Clean smarter with ONYX battery-powered floor scrubbers.

Built for performance and engineered for reliability, our scrubbers deliver deep, consistent cleaning—fast. Outfitted with maintenance-free AGM batteries, rugged cast aluminum heads, and durable steel frames, they're designed to tackle the toughest grime with ease.

High-capacity solution and recovery tanks keep you cleaning longer with fewer stops, while powerful vacuum motors and oversized squeegees leave floors spotless, dry, and ready to impress.

Simple to operate and easy to service, ONYX scrubbers help your team stay productive with less downtime and less training.

OVERSIZED SOLUTION TANKS

Large capacity solution and recovery tanks.

QUIET AND RELIABLE

500 watt vacuum motor
< 63 dBA sound level

MAINTENANCE FREE BATTERIES

Fully sealed AGM
Maintenance Free Batteries
with 3-5 hour runtime.



HEAVY DUTY CONSTRUCTION

Reinforced Steel
Frame & LDPE Body.
Cast Aluminum
Heads & wheel hubs.



HASSLE-FREE MAINTENANCE

Simplified electrical
systems for easy service
and repair.

Battery Walk Behind Floor Scrubbers

Battery Ride-on Floor Scrubbers

ALL SCRUBBERS ARE
SOLD STANDARD WITH
DRIVER AND PADS



	<i>DX15</i>	<i>DX20T</i>	<i>DX26T</i>	<i>DX32T</i>	<i>RX20</i>	<i>RX26</i>	<i>RX32</i>	<i>RX34</i>
CLEANING WIDTH	15" Brush/Pad	20" Brush/Pad	26" Brush/Pad	32" Brush/Pad	20" Brush/Pad	26" Brush/Pad	32" Brush/Pad	34" Brush/Pad
SQUEEGEE WIDTH	24"	32"	42"	42"	32"	42"	42"	42"
PERFORMANCE	Up to 16,000 Sq Ft Per Hour	Up to 24,000 Sq Ft Per Hour	Up to 35,000 Sq Ft Per Hour	Up to 43,000 Sq Ft Per Hour	Up to 35,000 Sq Ft Per Hour	Up to 46,000 Sq Ft Per Hour	Up to 56,000 Sq Ft Per Hour	Up to 62,500 Sq Ft Per Hour
VACUUM MOTOR	500 watt	500 watt	500 watt	500 watt	500 watt	500 watt	500 watt	500 watt
SOUND LEVEL	< 63 dBA	< 63 dBA	< 63 dBA	< 63 dBA	< 63 dBA	< 63 dBA	< 63 dBA	< 63 dBA
BRUSH/PAD SPEED	180 RPM	180 RPM	180 RPM	180 RPM	180 RPM	180 RPM	180 RPM	180 RPM
BRUSH/PAD SIZE	15"	20"	13" x 2	16" x 2	20"	13" x 2	16" x 2	17" x 2
RUN TIME	3-4 Hours	3-4 Hours	4-5 Hours	4-5 Hours	3-4 Hours	5-6 Hours	5-6 Hours	5-6 Hours
HEAD PRESSURE	25 lbs	50-90 lbs	100 lbs	100 lbs	100 lbs	100 lbs	100 lbs	125 lbs
SOLUTION CAPACITY	7 Gallons	14 Gallons	17 Gallons	17 Gallons	17 Gallons	25 Gallons	25 Gallons	47 Gallons
RECOVERY CAPACITY	8 Gallons	16 Gallons	23 Gallons	23 Gallons	20 Gallons	34 Gallons	34 Gallons	51 Gallons
WEIGHT	205 lbs	290 lbs	460 lbs	460 lbs	485 lbs	940 lbs	950 lbs	1,270 lbs
BATTERY CAPACITY	24 volt, 2 x 12v 125 Ah	12 volt, 125 Ah	24 volt, 4 x 6v 270 Ah	24 volt, 4 x 6v 270 Ah	24 volt, 2 x 12v 125 Ah	24 volt, 4 x 6v 270 Ah	24 volt, 4 x 6v 270 Ah	36 volt, 6 x 6v 270 Ah
DIMENSIONS	24"W x 40"L x 41"H	20"W x 49"L x 44"H	28"W x 53"L x 45"H	33"W x 53"L x 45"H	24"W x 49"L x 43"H	32"W x 53"L x 45"H	32"W x 53"L x 45"H	37"W x 67"L x 48"H

Cylindrical Machines

ALL SCRUBBERS ARE
SOLD STANDARD WITH
DRIVER AND PADS



	<i>DX20C</i>	<i>DX26C</i>	<i>RX30C</i>
CLEANING WIDTH	20" Cylindrical Brush	26" Cylindrical Brush	30" Cylindrical Brush
SQUEEGEE WIDTH	32"	42"	42"
PERFORMANCE	Up to 24,000 Sq Ft Per Hour	Up to 35,000 Sq Ft Per Hour	Up to 56,000 Sq Ft Per Hour
VACUUM MOTOR	500 watt	500 watt	500 watt
SOUND LEVEL	< 63 dBA	< 63 dBA	< 63 dBA
CYLINDER BRUSH SPEED	620 RPM	620 RPM	620 RPM
CYLINDER BRUSH WIDTH	20" x 2	24" x 2	28" x 2
RUN TIME	3-4 Hours	4-5 Hours	5-6 Hours
SOLUTION CAPACITY	14 Gallons	17 Gallons	25 Gallons
RECOVERY CAPACITY	16 Gallons	23 Gallons	34 Gallons
WEIGHT	350 lbs	700 lbs	950 lbs
BATTERY CAPACITY	12 volt, 125 Ah	24 volt, 4 x 6v 270 Ah	24 volt, 4 x 6v 270 Ah
DIMENSIONS	20"W x 49"L x 44"H	28"W x 53"L x 45"H	32"W x 53"L x 45"H

LITHIUM POWER

LFP Lithium Battery Burnishers

Step into the future of burnishing with the SXi from ONYX. Imagine a high-performance machine crafted to deliver the pristine, lustrous gloss your clients demand—without the noise and fumes of propane or the underwhelming results of older electric models. Powered by advanced lithium technology, the SXi combines unmatched power with extended runtime, allowing you to cover large areas on a single charge while enjoying the freedom, convenience, and immense productivity gains of cordless operation—saving significant time and labor costs for your business. You’ll be blown away by the SXi’s whisper-quiet performance, smooth control, and patented dust collection system, which captures fine particles and improves indoor air quality for your clients. More than just a machine, the SXi is a tool designed specifically to elevate your business to new heights and help you achieve unmatched success—one beautiful floor at a time.

OVERSIZED SOLUTION TANKS

Large capacity 10 gallon solution tank.

HEAVY DUTY CONSTRUCTION

Reinforced Steel Frame & LDPE Body. Industrial grade bearings.

WHISPER QUIET

Perfect for professional, educational, and health care facilities.

SXi

LITHIUM POWERED BURNISHER

LITHIUM IRON PHOSPHATE (LFP) BATTERY TECHNOLOGY

Onboard smart battery charger. Lithium power. Fast recharge time.

5 HORSEPOWER MOTOR

Powerful performance to achieve “wet-look” gloss.

ADJUSTABLE PAD PRESSURE

Adjustable pad pressure with fine-tune increments. Variable motor/pad speed. Easy removable pad driver.

THE FUTURE STARTS WITH YOU

PRODUCT LINE SUMMARY

Lithium-ion Burnisher Configurations



	Burnisher Configuration	Stripper Configuration	Polisher Configuration
WORKING WIDTH	21", 24", or 27" Pad	21" Brush/Pad	27" Pad**
PERFORMANCE	Up to 34,000 Sq Ft Per Hour	Up to 8,000 Sq Ft Per Hour	Up to 8,000 Sq Ft Per Hour
MOTOR POWER	5 HP (3.75 kw)		
SOUND LEVEL	< 63 dBA		
PAD SPEED	1,050-1,800 RPM	600-1,000 RPM	600-1,000 RPM
RUN TIME (SINGLE)	2 Hours*		
RUN TIME (DOUBLE)	4 Hours*		
HEAD PRESSURE	20-120 lbs (variable)		
SOLUTION CAPACITY	10 Gallons		
WEIGHT	245 lbs	255 lbs	270 lbs
BATTERY CAPACITY (SINGLE)	60 AH = 4.32 kWh		
BATTERY CAPACITY (DOUBLE)	120 AH = 8.64 kWh		
DIMENSIONS	29"W x 64"L x 42"H		

* Under normal condition, actual runtime may vary.
** Configurations with 21" and 24" polish heads available upon request.

PROPANE FLOOR MACHINES

Propane Floor Strippers,
Burnishers and Polishers

Propane Burnishers are designed for speed and safety. Available in 21", 24", or 27" sizes, our propane machines burnish vinyl tile, terrazzo, and concrete floors.

The patented floating shroud eliminates airborne dust keeping store shelves clean and operators safe. The patented variable jet fuel system reduces emissions and is certified as 53% cleaner than any engine in its class.

NEAR ZERO EMISSIONS

Certified 100x below EPA
Carbon Monoxide stds
Lowest carbon emissions
in its class, by 53%.
On-board real-time
emissions monitoring with
SAM Safe Air Monitor.

FAST & RELIABLE

Tool-less pad
driver removal.
Quick wheel
& handle
adjustment.

BEST IN CLASS PRODUCTIVITY

Fuel system requires no
adjustments.
Internal vaporizer eliminates
regulator freezing.
In-line fuel filter.

HEAVY DUTY CONSTRUCTION

Reinforced Steel
Frame & LDPE Body.
Industrial grade
bearings.



Propane Floor Machines - Burnishers & Strippers



JX7-600
Burnisher

JX7-700
Burnisher

TX1
Stripper

TX7
Stripper

ZX7
Polisher

ZX30
Polisher

WORKING WIDTH	21", 24", or 27",	21", 24", or 27",	21"	27"	27"	30"
ENGINE	603cc 17 HP	708cc 19 HP	708cc 19 HP	708cc 19 HP	708cc 19 HP	708cc 17 HP
PERFORMANCE	Up to 34,000 Sq Ft Per Hour	Up to 34,000 Sq Ft Per Hour	Up to 8,000 Sq Ft Per Hour	Up to 10,000 Sq Ft Per Hour	Up to 34,000 Sq Ft Per Hour	Up to 27,000 Sq Ft Per Hour
SOUND LEVEL	< 87 dBA				< 87 dBA	
PAD SPEED	1200 to 2100 RPM			540 to 1080 RPM	1200 to 2100 RPM	530 to 2300 RPM
PAD SIZE	21", 24" & 27"			10" x 3	27"	11" x 3
RUN TIME	6 Hours Per 20 lb Cylinder			6 Hours Per 20 lb Cylinder	6 Hours Per 20 lb Cylinder	6 Hours Per 20 lb Cylinder
DIMENSIONS	28"W x 53"L x 40-48"H	28"W x 53"L x 40-48"H	21"W x 53"L x 40-48"H	30"W x 53"L x 40-48"H	28"W x 53"L x 40-48"H	34"W x 75"L x 42"H
FRAME	Powder Coated Reinforced Steel				Powder Coated Reinforced Steel	
WEIGHT	280 lbs	295 lbs	450 lbs	450 lbs	295 lbs	620 lbs
IGNITION SYSTEM	12v Electric Start				12v Electric Start	
FUEL TANK	20lb Steel with Overfill Protection Device Installed				20lb Steel with Overfill Protection Device Installed	



We believe that tomorrow can, and will, be better than today.

But, it takes a hero to change the world.

It takes you.

BECOME HERO™



T1

LOW SPEED FLOOR MACHINE

HEAD SIZES	13, 17, 20 Inch (interchangeable)
MOTOR POWER	1.5 HP
RPM	175
VOLTAGE	110-120V (AC)
POWER CORD	50 ft, 14/3 STO Yellow
TRANSMISSION	Triple Planetary, Cast Iron w/ Hardened Steel Gears
HANDLE LENGTH	42 Inch
SOLUTION TANK	4 Gal Tank Available
WEIGHT KIT	28 & 50 Lb Kits Available
DUST PORT & SKIRT	Available
HEADLIGHT	LED Light Strip Included

LED LIGHT

Brightens work area for safety and comfort.

VOLTAGE

110-120V (AC)

WATER TANK

4 Gallon water tank.

ADDITIONAL WEIGHT KIT

28 lb weight kit.

INDUSTRIAL

Square tubing handle.

VERSATILE

Quickly swap between 20, 17, 13 inch.

TRANSMISSION

Triple Planetary, Cast Iron w/ Hardened Steel Gears

SAFE & CLEAN

Skirt for dust and splash control.

R25

WET DRY VACUUM

RECOVERY VOLUME	True 25 Gal
MOTOR POWER	1250 W (1.7 HP)
SQUEEGEE WIDTH	29 inch
VOLTAGE	110-120V (AC)
POWER CORD	50 ft, 14/3 SJTOW, Yellow
INLET HOSE	1.5 Inch
DRAIN HOSE	1.5 Inch
TIP & POUR DRAIN	4.0 Inch
TRANSPORT WHEEL	10 inch, Solid Rubber
HEADLIGHT	Dual LED Headlight Available

INNOVATIVE

Air enters head high above water, to eliminate water ingestion.

ERGONOMIC

Comfort grips.

FAST DRAIN

Drain hose AND Tip & Pour.

HEADLIGHTS

Brightens work area for safety and comfort.

VOLTAGE

110-120V (AC).

HUGE

Industry-best 25 gallons recovery.

TOOLESS

Squeegee blade replacement.

OPTIMIZED

Extreme water pickup.



ONYX™

THE FUTURE STARTS WITH YOU



SCAN ME

12605 Commerce Station Dr • Suite 700
Huntersville, NC 28078
704.827.9368

ONYXSOLUTIONS.COM
sales@onyxsolutions.com